



Heat Shrink Tube(Dual Wall)

Liansi-Heat Shrink Tube(Dual Wall)

Dual Wall 4:1



*Shrinking ratio 4:1

*Chemical and Solvent resistant

*Multi-purpose insulator



Application

Medium wall adhesive lined shrink tubing for low voltage power cables.

- Designed for shipbuilding, Germanische Lloyd approved
- Flame retarded
- UV and weather resistant
- Excellent mechanical

Heat Shrinkable Tubing 4:1 - Flame retardant

This kind of heat shrink tube offers superior environmental performance for a wide assortment of electronic wiring components including wire splices, wire and cable bundles, and harness breakout in automotive, trucks, and marine cable and other industrial fields.

Technical Data

| | |
|--------------------------|------------------------------------|
| Material | Polyethylene |
| Shrinking ratio | 4:1 |
| Start shrunk temperature | 70°C |
| Longitudinal shrinkage | 5% |
| Flammability | VW-1 |
| Standard color | Black |
| Operating range | -45°C±125°C |
| Certificate | UL, CSA, RoHS, REACH, Halogen Free |
| Tool | Heat gun |

Datasheet

| Spec. (mm) | ID Before shrunk | After shrunk | | | Packing(m/roll) | Inch |
|------------|------------------|--------------|----------------|--------------------|-----------------|--------|
| | | ID | Wall thickness | Adhesive thickness | | |
| 4.0 | 4 | 1.0 | 1.0±0.15 | 0.4±0.15 | 200 | 5/32" |
| 6.0 | 6 | 1.5 | 1.1±0.15 | 0.4±0.15 | 100 | 1/4" |
| 8.0 | 8 | 2.0 | 1.2±0.15 | 0.5±0.15 | 50 | 5/16" |
| 12.0 | 12 | 3.0 | 1.4±0.15 | 0.6±0.15 | 1.22m/pc | 1/2" |
| 16.0 | 16 | 4.0 | 1.7±0.15 | 0.6±0.15 | 1.22m/pc | 5/8" |
| 20.0 | 20 | 5.0 | 2.0±0.15 | 0.6±0.15 | 1.22m/pc | 25/32" |
| 24.0 | 24 | 6.0 | 2.1±0.15 | 0.6±0.15 | 1.22m/pc | 1" |
| 32.0 | 32 | 8.0 | 2.4±0.15 | 0.7±0.15 | 1.22m/pc | 1-1/2" |
| 52.0 | 52 | 13.0 | 2.4±0.15 | 0.7±0.15 | 1.22m/pc | 2" |

Unit:mm