



Liansi-PET

PET Braided Sleeving

Color catalogue



***Economical and easy to install**

***Expands up to 150%**

***Cut and Abrasion Resistant**



Application

LS braided sleeve is flame-retardant and halogen-free. This material has the advantage of flexible, durable. It is widely used on the field of electronics, automotive, wire harness, computer cable, A/V cable, office/house using, industrial wire/hose, aerospace, military where make it efficiency and valuable. This sleeving has expandable character, most sizes are nearest.

Technical Data

Material	Polyester
Operating range	-50°C±150°C
Melt point	250±5°C
Flammability	VW-1
Standard color	Black and grey
Certificate	UL, CSA, RoHS, REACH, Halogen Free
Cutting tool	Hot knife

Datasheet

Nominal size(W)		Part No.	Expanded range		Packing Standard Spool
Inch	mm		Min.(I)	Max.(O)	
1/8"	2	LS-PET1632013	1	6	500m
4/25"	4	LS-PET2432015	2	8	500m
1/4"	6	LS-PET3232011	3	9	500m
5/16"	8	LS-PET4032009	5	16	500m
2/5"	10	LS-PET4832010	7	19	300m
1/2"	12	LS-PET4832008	8	24	300m
3/5"	15	LS-PET5632008	10	27	200m
4/5"	20	LS-PET7232510	14	30	200m
1"	25	LS-PET7232508	18	35	200m
1-1/4"	30	LS-PET9632507	20	50	100m
1-3/5"	40	LS-PET120425010	30	60	100m
1-3/4"	45	LS-PET12042509	35	75	100m
2"	50	LS-PET12042507	40	80	100m
2-1/2"	64	LS-PET14842506	45	105	100m
3"	76	LS-14852506	64	120	100m



Unit:mm